

## **Automotive Glass Sliver Paste**

					$\rightarrow$			
PART NUMBER	AG CONTENT	APPLICATION	ROHS	560 580 6		EMPERATUR		RESISTANCE (mΩ)
SP 60	60%	Tempered Glass	Unleaded	,4,1				± 8.2
SP 75	75%	Tempered Glass	Unleaded				>/	± 7.5
SP 80	80%	Tempered Glass	Unleaded					± 2.8
SP 85	85%	Tempered Glass	Unleaded			<b>©</b>		± 2.2
SP 80L	80%	Laminated Glass	Unleaded					± 2.8
SP 85L	85%	Laminated Glass	Unleaded		4,5		0	± 2.2

## Limitation of Warranty and Liability

We believes that the information shared in this document is accurate at the time of its publication. It is not a product specification, either in whole or in part. Users are responsible for determination of the suitability of this product and for testing in specific applications. Please test first before use. Nothing in this document shall be construed as a license for use that infringes upon any property rights of any third party. Please refer to the Safety Data Sheet (SDS) for safe use, handling and disposal information.



## 汽车玻璃银浆

编号	含银量	应用	ROHS	烤烧温度 560 580 600 620 640 660 680 700 73	20 740	电阻 (mΩ)
SP 60	60%	钢化玻璃	不含铅			± 8.2
SP 75	75%	钢化玻璃	不含铅			± 7.5
SP 80	80%	钢化玻璃	不含铅			± 2.8
SP 85	85%	钢化玻璃	不含铅			± 2.2
SP 80L	80%	夹层玻璃	不含铅		0	± 2.8
SP 85L	85%	夹层玻璃	不含铅			± 2.2

## 保证和责任限制

我们确信本文件公布时所共享的信息是准确的。它不是全部或部分的产品规格。用户负责确定本产品的适用性,并在特定应用中进行测试。使用前请先测试。本文件中的任何内容均不得解 释为侵犯任何第三方财产权利的使用许可。有关安全使用、处理和处置信息,请参阅安全数据表(SDS)。